

May 2017

# SUPERIOR GROUT SEALER TECHNICAL APPLICATION GUIDE

## DESCRIPTION

### SEALS & PROTECTS GROUT

- Use on cement based wall and floor porous grout joints for ceramic tile and natural tile installations
- Effective for interior and exterior applications

**Superior Grout Sealer** is a solvent free grout sealer that resists water, and oil based contaminants. Simplifies maintenance and does not change the appearance of the grout whilst allowing for moisture vapour transmission. Suitable for use on cement based wall and floor grout joints for ceramic tile and natural tile installations. Effective for interior and exterior applications.

## DIRECTIONS FOR USE

- 1) Read entire label before using.
- 2) For new installations sealer can be applied 48 hours after grouting.
- 3) Grout joints must be clean, dry and free of existing sealers or coatings.
- 4) Apply using a soft-bristle paint brush or sponge applicator.
- 5) Apply second application, allowing a minimum of 30 minutes drying time between coats.
- 6) After 2 hours conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an additional coat. Wait 2 hours and repeat the test.
- 7) Ready for surface traffic 2 hours after final coat. Sealed area should be kept dry for minimum of 12 hours. Achieves full cure in 24 hours.
- 8) Clean applicator tools with water after each use.
- 9) May be reapplied as needed to grout joints that are clean.

**Always test a small area according to application instructions, with a 24-hour cure time to determine desired results.**

**LIMITATIONS:** Do not allow sealer to dry on tile surface because a residue will be visible. Do not allow sealer to come in contact with any non-recommended surface. Sealer will not prevent surface wear from etching from acids or caustic chemicals.

## EXPECTED WEAR

Will vary depending on porosity and texture of surface, type of area, surface wear, frequency and type of maintenance products used. The expected wear is up to 5 years. Extreme weather conditions, harsh cleaning methods and high-alkaline or solvent-based cleaners will affect the longevity and performance.

## USAGE GUIDELINES

Drying Time	Applications/ Coats	Application Method	Dilution
2 hours	1-3 coats	Brush/ Sprayer/ Sponge	Undiluted

## STORAGE INFORMATION

Close container after use. Store in original container only. Store and use in temperature between 10°C and 27°C. Protect unused, stored product from freezing.

## COVERAGE

Approximately 15m<sup>2</sup> to 60m<sup>2</sup> per coat per 500ml, depending on porosity of grout joint and method of application. For example, on a 30 x 30 cm tile with a 3mm grout joint a 500ml bottle will cover approximately 40m<sup>2</sup> for 2 coat application.

## PRECAUTIONS

**KEEP OUT OF THE REACH OF CHILDREN & PETS**

- S1/2** Keep locked up and out of reach of children.
- S26** In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S46** If swallowed, seek medical advice immediately and show this container or label. Rubber gloves and eye protection should be worn during application.

Product SDS sheet available to download from our website.



Made in the UK 