

May 2017

# SUPERIOR STONE ENHANCER TECHNICAL APPLICATION GUIDE

### DESCRIPTION

#### **ONE-STEP COLOUR INTENSIFIER SEALER**

- Enhances natural colour & texture
- Suitable for all types of natural stone surfaces
- Protects against staining from oil & water
- Suitable for internal & external use

Superior Stone Enhancer is a premium grade water based stone and masonry enhancing sealer that impregnates to protect against oil and water based stains, whilst enhancing the natural stone colours, leaving a matt finish.

Superior Stone Enhancer can be used for internal and external application, suitable for the application to all porous textured stone and masonry surfaces. Not recommended for use on highly polished, ceramic/glazed or non-porous surfaces.

# **DIRECTIONS FOR USE**

- Before application the surface must be completely clean and dry, apply an even coat with a low pressure sprayer, roller, natural fibre brush or sponge. Any excess sealer must be completely removed from the surface after 20-30 minutes, failure to remove the excess will lead to an unwelcome tacky, shiny finish.
- 2) Apply a second application approximately 45-60 minutes repeating the process. After application it is important that the stone surface is kept completely dry through the curing process, up to 72 hours. Any moisture or water left on the surface within this time may result in the sealer drying inconsistent showing hard to remove white patches.

**Please Note:** Areas not to be sealed must be protected with masking materials. It is strongly recommended that a small test area is completed before proceeding to ensure suitability for surface type.

# MAINTENANCE

Clean treated areas with Superior Tile & Stone Cleaner, do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

# COVERAGE

#### Up to 25m<sup>2</sup> per litre

This will depend on the porosity of surface. Check the surface after application to ensure full effectiveness of impregnator.

# USAGE GUIDELINES

Drying Time	Applications/ Coats	Application Method	Dilution
45-60 mins	1-2 coats	Brush/Sprayer Roller/Sponge	Undiluted

# KEEP OUT OF THE REACH OF CHILDREN & PETS H302: Harmful if swallowed.

H315: Causes skin irritation.

PRECAUTIONS

- H319: Causes serious eye irritation.
- P102: Keep out of reach of children.
- P262: Do not get in eyes, on skin, or on clothing.
- P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor. P332+313: If skin irritation occurs: Get medical advice. P337+313: If eye irritation persists: Get medical advice.

#### Product SDS sheet available to download from our website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.





# www.smartseal.co.uk

Smartseal UK Limited. Enquiries: 01268 722500 Email: contactus@smartseal.co.uk Unit 15 & 16 Annwood Lodge Business Park, Arterial Road, Rayleigh Essex SS6 7UA

