
SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Product Name: Crack Repair Compound
- Contains portland cement

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Use of the substance/mixture: Colouring and filling cracks in concrete surfaces
- Use advised against: No information available

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Smartseal UK Ltd
- Address of Supplier: Unit 15-16 Annwood Lodge Business Park, Rayleigh, Essex SS6 7UA
UK
- Telephone: +44 (0) 1268 722500
- Email: contactus@smartseal.co.uk

1.4 Emergency telephone number

- Emergency Telephone: +44 (0) 1268 722500
(Office hours only Mon– Fri 08:30 – 17:30)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- Classification (REGULATION (EC) No 1272/2008) [CLP/GHS]: Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Dam. 1, H318; STOT SE 3, H335
- Additional information: For full text of Hazard- and EU Hazard-statements: see section 16

2.2 Label elements



- Signal Word: Danger
- Hazard statements
 - H315 - Causes skin irritation.
 - H317 - May cause an allergic skin reaction.
 - H318 - Causes serious eye damage
 - H335 - May cause respiratory irritation.
- Precautionary statements
 - P260 - Do not breathe dust
 - P264 - Wash thoroughly after handling.
 - P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 - P302+P352+P333+P313 - IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
 - P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

SECTION 2: Hazards identification (...)

contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P501 - Dispose of contents/container to an authorised waste collection point

- Supplemental Hazard Information (EU)
EUH203 - Contains chromium (VI). May produce an allergic reaction.

2.3 Other hazards

- Not a PBT according to REACH Annex XIII
- Not a vPvB according to REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1 Substances

3.2 Mixtures

Chemical Name	Conc.	CAS No.	EC No.	Classification (REGULATION (EC) No 1272/2008) [CLP/GHS]	REACH Registration Number	WEL /OEL
quartz (SiO ₂); crystalline silica flour	50 - 70%	14808-60-7	238-878-4	Not Classified	Exempted	Yes
cement, portland	20 - 30%	65997-15-1	266-043-4	Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Dam. 1, H318; STOT SE 3, H335	01-2119457435 -35-XXXX	Yes
carbon black	< 1%	1333-86-4	215-609-9	Not Classified	-	Yes
iron oxides	< 1%	-	-	Not Classified	-	Yes
titanium dioxide	< 1%	13463-67-7	236-675-5	Not Classified	01-2119489379 -17-XXXX	Yes
limestone	< 1%	1317-65-3	215-279-6	Not Classified	-	Yes

SECTION 4: First aid measures

4.1 Description of first aid measures

- Contact with eyes
If substance has got into eyes, immediately wash out with plenty of water for several minutes
Irrigate eyes thoroughly whilst lifting eyelids
Remove contact lenses, if present and easy to do. Continue rinsing.
Get immediate medical advice/attention.
- Contact with skin
Take off contaminated clothing and wash it before reuse.
Wash affected area with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention.
- Ingestion
Rinse mouth with water (do not swallow)
Do NOT induce vomiting.
Get immediate medical advice/attention.
- Inhalation
If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
Keep warm and at rest, in a half upright position. Loosen clothing
Apply artificial respiration only if patient is not breathing but do not use mouth to mouth resuscitation

SECTION 4: First aid measures (....)

Immediately call a POISON CENTER or doctor/physician.

4.2 Most important symptoms and effects, both acute and delayed

- Contact with eyes
May cause severe damage with formation of corneal ulcers and permanent impairment of vision.
- Contact with skin
May cause an allergic skin reaction.
Dry material causes skin irritation, wet material causes skin burns.
- Ingestion
May cause gastro-intestinal irritation
May cause burns to mouth and throat
- Inhalation
May cause respiratory tract irritation.
May cause breathing difficulty

4.3 Indication of any immediate medical attention and special treatment needed - Treat symptomatically

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Not flammable. In case of fire use extinguishing media appropriate to surrounding conditions

5.2 Special hazards arising from the substance or mixture

- Corrosive

5.3 Advice for firefighters

- Collect contaminated fire extinguishing water separately. This **MUST** not be discharged into drains. Prevent fire extinguishing water from contaminating surface or ground water.
- No special precautions are required for this product

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Rescuers should take suitable precautions to avoid becoming casualties themselves
- Personal precautions for non-emergency personnel: Do not breathe dust; Avoid contact with skin and eyes; Wear protective clothing as per section 8; Wash thoroughly after handling.
- Personal precautions for emergency responders: Wear protective clothing as per section 8

6.2 Environmental precautions

- Avoid release to the environment.
- Do not allow to enter public sewers and watercourses
- If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3 Methods and material for containment and cleaning up

- Collect as much as possible in clean container for reuse or disposal
- **Dry cement**

Use clean up methods such as vacuum clean-up or vacuum extraction (Industrial portable units, equipped with high efficiency air filters (EPA and HEPA filters, EN 1822-1:2009) or equivalent technique) which do not cause airborne dispersion. Never use compressed air. Alternatively, wipe-up the dust by mopping, wet brushing or by using water sprays or hoses (fine mist to avoid that the dust becomes airborne) and remove slurry. If not possible, remove by slurring with water (see wet cement). When wet cleaning or vacuum cleaning is not possible and only dry cleaning with brushes can be done, ensure that the workers wear the appropriate personal protective equipment and prevent dust from spreading. Avoid inhalation of cement and contact with skin. Place spilled materials into a container. Solidify before disposal.

SECTION 6: Accidental release measures (....)

- **Wet cement**

Clean up wet cement and place in a container. Allow material to dry and solidify before disposal

6.4 Reference to other sections

- See section(s): 7,8 &13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Prevent formation of dust
- Use only outdoors or in a well-ventilated area.
- No respiratory protection is needed if ventilation/extraction is adequate, otherwise wear approved dust mask
- Do not eat, drink or smoke when using this product.
- Do not get in eyes, on skin, or on clothing.
- Wear protective gloves
- Wear goggles giving complete eye protection
- Wash contaminated clothing before reuse.
- Contaminated work clothing should not be allowed out of the workplace.
- Wash thoroughly after use

7.2 Conditions for safe storage, including any incompatibilities

- Keep only in the original container
- Keep container tightly closed, in a cool, well ventilated place
- Protect from moisture
- Opened containers should be carefully resealed and stored in an upright position

7.3 Specific end use(s)

Colouring and hardening the surface of freshly placed concrete

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

- quartz (SiO₂); crystalline silica flour
WEL (long term) 0.1 mg/m³ (respirable crystalline silica, UK)
- cement, portland
WEL (long term) 10 mg/m³ (inhalable dust, UK)
WEL (long term) 4 mg/m³ (respirable dust, UK)
- carbon black
WEL (long term) 3.5 mg/m³ (UK)
WEL (short term) 7 mg/m³ (UK)
DNEL (inhalational) 500 ug/m³ Industry, Long Term, Local
Effects PNEC aqua (freshwater) 1 mg/l
PNEC aqua (intermittent releases, freshwater) 10 mg/l
PNEC aqua (marine water) 100 ug/l
PNEC aqua (intermittent releases, marine water) 1
mg/l - iron oxide
WEL (long term) 1 mg/m³ (iron salts as Fe, UK)
WEL (short term) 2 mg/m³ (iron salts as Fe, UK)
- titanium dioxide
WEL (long term) 10 mg/m³ (total inhalable, UK)
WEL (long term) 4 mg/m³ (respirable, UK)

SECTION 8: Exposure controls/personal protection (....)

- limestone
 - WEL (long term) 10 mg/m³ (inhalable dust, UK)
 - WEL (long term) 4 mg/m³ (respirable dust, UK)

8.2 Exposure controls

- Selection and use of personal protective equipment should be based on a risk assessment of exposure potential
- If practicable, engineering controls should be provided where airborne concentrations exceed exposure limits
- No respiratory protection is needed if ventilation/extraction is adequate, otherwise wear approved dust mask
- Where a reusable half mask respirator is required, use EN 140 mask and EN 143 particle filter, or EN 1827
- Where a full face mask respirator is required, use EN 136, with particle filter EN 143
- Wear goggles giving complete eye protection
- Wear protective gloves. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and standard EN 374.
- The selection of a suitable glove depends on work conditions and whether the product is present on its own or in combination with other substances. Breakthrough time is dependent on the characteristics of the brand of glove used and the supplier should be consulted.
- Use a suitable barrier cream to protect skin
- Wear suitable protective clothing
- Wear boots
- Contaminated work clothing should not be allowed out of the workplace.
- Contaminated clothing should be laundered before reuse
- Use good personal hygiene practices
- Do not eat, drink or smoke when using this product.
- Wash thoroughly after handling.
- Ensure eyewash stations and safety showers are nearby

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

- Appearance: Coloured; powder
- Odour: None
- Odour threshold: No information available
- pH: 12 - 14 (aqueous solution)
- Melting point/freezing point: >1250 °C (cement)
- Initial boiling point and boiling range: No information available
- Flashpoint: No information available
- Evaporation Rate: No information available
- Flammability (solid,gas): Not flammable
- Upper/lower flammability or explosive limits: Not applicable
- Vapour Pressure: Not applicable
- Vapour Density: Not applicable
- Relative Density: 2.8 - 3.2
- Solubility(ies): Negligible in water
- Partition Coefficient (n-Octanol/Water): Not applicable
- Autoignition Temperature: No information available
- Decomposition temperature: No information available
- Viscosity: No information available
- Explosive Properties: Non-explosive

SECTION 9: Physical and chemical properties (....)

- Oxidising properties: Not oxidising

9.2 Other information

- No information available
-

SECTION 10: Stability and reactivity

10.1 Reactivity

- No hazardous reactions known if used for its intended purpose

10.2 Chemical stability

- Considered stable under normal conditions

10.3 Possibility of hazardous reactions

- No hazardous reactions known if used for its intended purpose

10.4 Conditions to avoid

- Avoid formation of dust
- Keep away from moist air or water

10.5 Incompatible materials

- Incompatible with aluminium
- Incompatible with acid
- Incompatible with ammonia solution
- Incompatible with oxidizing substances

10.6 Hazardous decomposition products

- Refractories containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional.
-

SECTION 11: Toxicological information

11.1 Information on toxicological effects

- Acute Toxicity
Based on available data, the classification criteria are not met
- Skin corrosion/irritation
Causes skin irritation.
Classification based on calculation and concentration thresholds
- Serious eye damage/irritation
Causes serious eye damage
Classification based on calculation and concentration thresholds - Respiratory or skin sensitisation
May cause an allergic skin reaction.
Classification based on calculation and concentration thresholds
- Germ cell mutagenicity
No evidence of mutagenic effects
- Carcinogenicity
No evidence of carcinogenic effects
- Reproductive toxicity
No evidence of reproductive effects
- Specific target organ toxicity (STOT) - single exposure
STOT SE 3
May cause respiratory irritation.
Classification based on calculation and concentration thresholds

SECTION 11: Toxicological information (....)

- Specific target organ toxicity (STOT) - repeated exposure Based on available data, the classification criteria are not met Long term exposure to crystalline silica can cause silicosis
 - Aspiration hazard
Based on available data, the classification criteria are not met
 - Contact with eyes
May cause severe damage with formation of corneal ulcers and permanent impairment of vision.
 - Contact with skin
Dry material causes skin irritation, wet material causes skin burns.
May cause dermatitis
 - Ingestion
May cause burns to mouth and throat
May cause gastro-intestinal irritation
Causes nausea/vomiting
 - Inhalation
Effect may vary from irritation of the nasal mucous membrane to severe lung irritation.
Long term exposure to crystalline silica can cause silicosis
-

SECTION 12: Ecological information

12.1 Toxicity

- Based on available data, the classification criteria are not met

12.2 Persistence and degradability

- Not readily biodegradable

12.3 Bioaccumulative potential

- No information available

12.4 Mobility in soil

- No information available

12.5 Results of PBT and vPvB assessment

- Not a PBT according to REACH Annex XIII
- Not a vPvB according to REACH Annex XIII

12.6 Other adverse effects

- May cause adverse effects in the aquatic environment due to high pH
-

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- For disposal, harden with water and dispose of the hardened product as concrete waste.
- Disposal should be in accordance with local, state or national legislation
- Dispose of contents/container to an authorised waste collection point

13.2 Classification

- The waste must be identified according to the List of Wastes (2000/532/EC)
-

SECTION 14: Transport information

Not classified as hazardous for transport

14.1 UN number

SECTION 14: Transport information (....)

- UN No.: Not applicable
 - 14.2 UN proper shipping name
 - Proper Shipping Name: Not applicable
 - 14.3 Transport hazard class(es)
 - Hazard Class: Not applicable
 - 14.4 Packing group
 - Packing Group: Not applicable
 - 14.5 Environmental hazards
 - Not applicable
 - 14.6 Special precautions for user
 - No special precautions are required for this product
 - 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code
 - Not applicable
 - 14.8 Road/Rail (ADR/RID)
 - Proper Shipping Name: Not applicable
 - ADR UN No.: Not applicable
 - ADR Hazard Class: Not applicable
 - ADR Packing Group: Not applicable
 - Tunnel Code: Not applicable
 - 14.9 Sea (IMDG)
 - Proper Shipping Name: Not applicable
 - IMDG UN No.: Not applicable
 - IMDG Hazard Class: Not applicable
 - IMDG Pack Group.: Not applicable
 - 14.10 Air (ICAO/IATA)
 - Proper Shipping Name: Not applicable
 - ICAO UN No.: Not applicable
 - ICAO Hazard Class: Not applicable
 - ICAO Packing Group: Not applicable
-

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - This safety data sheet is provided in compliance with REACH Regulation (EC) No 1907/2006 as amended by Regulation (EU) 2015/830
 - Regulation (EC) No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) applies in Europe
 - 15.2 Chemical safety assessment
 - A REACH chemical safety assessment has not been carried out
-

SECTION 16: Other information

The above information is believed to be correct but does not purport to be all inclusive and shall only be used as a guide. The company will not be held liable for any damage resulting from handling or from contact with this product.

SECTION 16: Other information (....)

Sources of data: Information from published literature and internal company data

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

- Skin Irrit. 2, H315: Classification based on calculation and concentration thresholds
- Skin Sens. 1B, H317: Classification based on calculation and concentration thresholds
- Eye Dam. 1, H318: Classification based on calculation and concentration thresholds
- STOT SE 3, H335: Classification based on calculation and concentration thresholds

Text not given with phrase codes where they are used elsewhere in this safety data sheet:

- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H318: Causes serious eye damage
- H335: May cause respiratory irritation

Acronyms

- CAS: Chemical Abstracts Service
- DNEL: Derived No-Effect Level
- EC: European Community
- EC50: Effective Concentration, 50%
- GHS: Globally Harmonised System
- LC50: Lethal Concentration, 50%
- LD50: Lethal Dose, 50%
- NOAEL: No observed adverse effect level
- OEL: Occupational Exposure Limit
- PBT: Persistent, Bioaccumulative and Toxic
- PNEC: Predicted No-Effect Concentration
- REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
- STOT RE: Specific Target Organ Toxicity Repeated Exposure
- STOT SE: Specific Target Organ Toxicity Single Exposure
- vPvB: very Persistent and very Bioaccumulative
- WEL: Workplace Exposure Limit

--- end of safety datasheet ---
