

Technical Data – Imprinted Concrete Silk

(90.41) E (G)

PRODUCT DESCRIPTION

Imprinted Concrete Silk is a pre-mixed, colourless blend of high-grade acrylic resin polymers and aromatic solvents.

PURPOSE

To impregnate **Imprinted Concrete** and combine the benefits of curing, hardening, dust proofing and sealing as well as leaving a wet look sheen finish.

SPECIAL PROPERTIES

- Hardens & seals concrete permanently
- Special blend of polymers do not soften in hot temperatures nor become brittle in freezing conditions
- High viscosity ensures full penetration into the dense surface matrix creating a true in-surface seal (ISS)
- Non-reemulsifiable, non-blooming when wet
- 100% inter-coat adhesion
- Curing Agent – allows concrete moisture emigration prior to reaching full hardness
- Non-yellowing
- Anti-carbonising agent
- Mechanical bond with surface matrix prevents delamination
- Tough, durable and hard wearing
- Designed to bring out and enhance the full depth of colour and leave a wet look sheen finish
- Petrol, Diesel, Oil & Grease resistant

APPLICATION INSTRUCTIONS

Bush slab to remove any dirt or debris. It is recommended that Smartseal Imprinted Concrete Sealer is applied with a Sealing Broom. The first application must be brushed into the surface whilst avoiding pooling, and allowed to dry past tacky prior to applying the second coat. Avoid application in strong, direct sunlight - do not apply if rain is likely within 8 hours of application.

Deicing salts should not be applied directly on Smartseal block paving or concrete sealers. Salt chemically reduces the temperature at which water freezes and will result in water ingress into the concrete. Subsequent freezing may result in the concrete seal being broken by the expansion of water as it freezes and white pitted areas may become visible.

****If using Smartseal Colour Tints, please select MATT imprinted concrete sealer instead of Silk****

APPROXIMATE COVERAGE

Average coverage: 4 to 6 m² per litre (dependent on condition).

STORAGE

Store in a cool, dry place.

23.09.2023

PACKAGING

5 & 25ltr U.N. 1993 approved drums.

TEST DATA

Sealer has been tested by the TRL (Transport Research Laboratory) and certified that it meets the SRV (Skid Resistance Value) for all categories of paving for local authority pedestrian areas and when heavily trafficked is suitable for special applications where risks of skidding are high as laid down in the UK Highway Authorities Tender Specification. Copies available on request.

SPECIFICATION CLAUSE

"The Sealer shall have been produced in minimum batch sizes of 1000 litres in accordance with an accredited BS5750 ISO9001 Quality Assurance System. All the work shall be carried out in accordance with the manufacturers current technical data sheet, specification and instructions for use."

HEALTH AND SAFETY

Flammable liquid. Do not smoke. Keep application area well ventilated. Wear respirator when applying. Flash point 42°C (Abel-Closed Cup). Refer to Safety Data Sheet for further information.

TECHNICAL SERVICES

For further information, call our technical dept on:-

Φ UK (01268) 722 500

Φ International +44(0)1268 722 500

e-mail contactus@smartseal.co.uk
Website www.smartseal.co.uk

Warranty

SmartSeal UK Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst SmartSeal UK Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

Manufactured by:

SmartSeal UK Ltd

Unit 3, 65-67 Cutlers Rd, South Woodham Ferrers,
Chelmsford CM3 5WA, United Kingdom

www.smartseal.co.uk

contactus@smartseal.co.uk