SmartSeal Oil Stain Remover

For Tarmac And Ashphalt

A new approach to the removal of oil stains on Tarmac and Asphalt oil contaminated surfaces.


SmartSeal Oil Stain Remover is a biological oil stain remover that rapidly removes and digest soil contamination.

Will not erode or degrade Tarmac or Asphalt surfaces.

KEY PROPERTIES Containing a blend of biodegradable surfactants ,biological enzymes and friendly bacteria to digest oil stains to completion, **SmartSeal Oil Stain Remover** penetrates and lifts oil stains and will not degrade tarmac and asphalt surfaces.

- Perfect for driveways, patios, paths, roads and car park surfaces
- Biodegradable
 Biological
 Tarmac friendly
- **APPLICATION**
- Shake container before use (to put bacteria into suspension).
- Water wet the oil stain before applying SmartSeal Oil Stain Remover.
- Apply neat to the oil stain and brush in vigorously for 2-3 minutes.
- Leave for 10-15 minutes.
- Water rinse.

TECHNICAL DATA



Oil Stain **REMOVER**

BEFORE



DURING



AFTER

Appearance	Cream Liquid	VOC content	<5%
Bacterial count	2.0 x 10 7cfu/ml	Flash point	>93°C
SG	1.01	рН	~ 8.0
BOD 5 days	1,800,000 mgs O/L	BOD 20 days	3,200,000 mgs O/L

NOTE

- For best results or for when using on larger stains, cover the treated area with polythene sheeting ideally making a tent and keep in place for up to a week.
- Ensure the area remains damp, but not flooded. Doing this provides a warm and damp environment, giving the bacteria used in the oil remover the best conditions to grow and digest the oil into carbon dioxide and water. Oil stains degrade Tarmac and
- Asphalt leaving behind an etched surface which appears as a dark stain **–this cannot be removed**.
- Please note: It is not suitable for use on synthetic oils, hydraulic fluid and wood oils.

PACKAGING

Containers: 12 x 1 Litre, 4 x 5 Litre, 20 Litre, 200 Litreand 1000 Litre Kits: 1m2kit and 5m2kit (supplied with absorbent powder and instruction leaflet)

SAFE HANDLING AND STORAGE

Store in original containers and avoid extremes of temperature. For guidance on handling and disposal, see Safety Data Sheet.

Manufactured and supplied by

SmartSeal UK Ltd

Unit 3, 65-67 Cutlers Rd, South Woodham Ferrers, Chelmsford CM3 5WA

Tel: F +44 (0) 1268 722500
Email: contactus@smartseal.co.uk
Web: www.smartseal.co.uk

