

Issue Date 23/09/23

Natural Stone Dry Finish

UPDATED INSTRUCTIONS AND TECHNICAL GUIDANCE TIPS

Please read carefully in full before applying the product and always complete a test patch to check suitability for your surface. For technical support, please call 01268 722500 (Extension Technical Support).

DESCRIPTION

Natural Stone Sealer DRY FINISH

Suitable for popular natural stone types including sandstone, limestone, slate, quarry tile, travertine, granite & more

Quick drying easy application

Low odour water based formula

MATT EFFECT for minimal change of finish

Durable, stain-resistant protection

Natural Stone Dry Finish is a water based, synthetic impregnating sealer. It imparts excellent water repellency and stain resistance to natural stone surfaces without changing the surface appearance. **Natural Stone Dry Finish** is a water-based protective coating that creates a highly durable matt finish on all types of outdoor natural sandstone, slate, limestone and more. Once sealed it creates an invisible barrier that significantly reduces liquid absorption of the treated surface, reducing efflorescence / salts blooming, organic soiling and moss and algae growth, whilst allowing the stone the ability to "breathe" and transfer moisture vapour.

DIRECTIONS FOR USE

APPLICATION NOTE: Application on vertical surfaces should be to full saturation commencing at the bottom and working upwards. Do not apply in damp conditions and only apply to dry surfaces in temperatures above 13°C and no higher than 23°C. It is very important to make sure no rain is forecast for at least 8 hours after application.

Depending on the stone/surface, more than one coat may be required. For most porous stones, a 2nd lighter coat can be applied once touch dry (slightly wet). If over application does occur on either coats, excess sealer can be removed with a dry roller or sponge. Ensure this is done within 45 minutes.

1. Shake container well before use
2. Ensure that surface area is completely clean from dirt & grime.
3. Allow surface area to dry, will take 3 dry days depending on the weather.
4. Apply 1st coat to saturation by roller, sprayer or brush.
5. Apply 2nd lighter 'mist' coat (approx 45 minutes after 1st coat if suitable).
6. If over application does occur, please remove excess sealer with a dry sponge or cloth.
7. Avoid walking on surface 4 hours after application and 48 hours for heavy traffic.

COVERAGE

- Average coverage: 1st coat 4 - 8 m² per litre (4m² Sandstone- 8m² Slate & Granite) 2nd coat 8 - 16 m² per litre (dependant on porosity and finish of the surface)

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months. Always shake bottle well before use.



Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
2-3 Hours	1-2 coats	Roller/ Sprayer/Brush	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor. P332+313: If skin irritation occurs: Get medical advice. P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available upon request.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

