

Issue Date 23/09/23

Clay Tile Sealer - Colour Enhancer

UPDATED INSTRUCTIONS AND TECHNICAL GUIDANCE TIPS

Please read carefully in full before applying the product and always complete a test patch to check suitability for your surface. For technical support, please call 01268 722500 (Extension Technical Support).

DESCRIPTION

Clay Tile Sealer - Colour Enhancer

Suitable for Clay Tiles

Low odour water based formula

Colour Enhance Matt Finish

Durable, stain-resistant protection

Clay Tile Sealer - Colour Enhancer is a water based, synthetic impregnating sealer. It imparts excellent water repellency and stain resistance to clay surfaces without changing the surface appearance. **Clay Tile Sealer - Colour Enhancer** is a water-based protective coating that creates a highly durable matt finish on all clay tiles. Once sealed it creates an invisible barrier that significantly reduces liquid absorption of the treated surface, reducing efflorescence / salts blooming, organic soiling and moss and algae growth, whilst allowing the stone the ability to "breathe" and transfer moisture vapour.

DIRECTIONS FOR USE

PREPARATION: Prior to application of clay tile sealer or natural stone sealer ensure surfaces to be sealed are clean, dry and free from contamination. If algae or stains are present pre treat prior to cleaning with a appropriate cleaning product.

Always test product on-site, in an inconspicuous area, to ensure you fully are satisfied with the final appearance/colour of the surface.

APPLICATION: Shake container well before use. Apply by pressure sprayer, roller, sponge or brush. Application on vertical surfaces should be to full saturation commencing at the bottom and working upwards. Do not apply in damp conditions and only apply to dry surfaces in temperatures above 13°C and no higher than 23°C. It is very important to make sure no rain is forecast for at least 8 hours after application.

Applying one coat to saturation is normally sufficient. For best results, apply one coat to saturation. If porous (only once **touch dry**) apply 2nd lighter coat can be applied ('wet on wet' finish). If over application does occur on either coats, excess sealer can be removed with a dry roller or sponge. Ensure this is done within 45 minutes.

All equipment should be cleaned with water immediately after use.

COVERAGE

- Average coverage 10 m² per litre (dependant on porosity and finish of the surface)

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months. Always shake bottle well before use.



Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
2-3 Hours	1-2 coats	Roller/ Sprayer/Brush	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor. P332+313: If skin irritation occurs: Get medical advice. P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available upon request.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

