

Issue Date 23/09/23

Natural Stone Colour Enhancer

UPDATED INSTRUCTIONS AND TECHNICAL GUIDANCE TIPS

Please read carefully in full before applying the product and always complete a test patch to check suitability for your surface. For technical support, please call 01268 722500 (Extension Technical Support).

DESCRIPTION

Natural Stone Sealer Colour Enhancer

Suitable for popular natural stone types including sandstone, limestone, slate, quarry tile, travertine, granite. Quick drying easy application

Low Colour Enhance Matt Finish

Durable, stain-resistant protection

Natural Stone Colour Enhancer is the ideal outdoor sealer for paving, patio & paths. Quick drying, the natural stone colours will be highly enhanced with a very durable matt finish. The advanced polymerised formula is 100% breathable allows full vapour transmission to avoid moisture issues. Natural Stone Colour Enhancer is a water-based impregnating sealer that creates a long-lasting colour enhanced finish on all types of outdoor porous natural stone. Very easy to apply, it fully penetrates the stone to protect against water stains, organic soiling and algae growth.

DIRECTIONS FOR USE

APPLICATION NOTE: Application on vertical surfaces should be to full saturation commencing at the bottom and working upwards. Do not apply in damp conditions and only apply to dry surfaces in temperatures above 13°C and no higher than 23°C. It is very important to make sure no rain is forecast for at least 8 hours after application.

Depending on the stone/surface, more than one coat may be required. For most porous stones, a 2nd lighter coat can be applied once touch dry (slightly wet). If over application does occur on either coats, excess sealer can be removed with a dry roller or sponge. Ensure this is done within 45 minutes.

1. Shake container well before use
2. Ensure that surface area is completely clean from dirt & grime.
3. Allow surface area to dry, will take 3 dry days depending on the weather.
4. Apply 1st coat to saturation by roller, sprayer or brush.
5. Apply 2nd lighter 'mist' coat (approx 45 minutes after 1st coat if suitable).
6. If over application does occur, please remove excess sealer with a dry sponge or cloth.
7. Avoid walking on surface 4 hours after application and 48 hours for heavy traffic.

COVERAGE

- Average coverage: 1st coat 4 - 8 m² per litre (4m² Sandstone- 8m² Slate & Granite) 2nd coat 8 - 16 m² per litre (dependant on porosity and finish of the surface)

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months. Always shake bottle well before use.



Usage Guidelines

| Drying Time | Applications/Coats | Application Method | Dilution |
|-------------|--------------------|--------------------------|-----------|
| 2-3 Hours | 1-2 coats | Roller/ Sprayer/Brush | Undiluted |

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.

P332+313: If skin irritation occurs: Get medical advice.

P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available upon request.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

