

Issue Date 23/09/23

# Sandstone Ultimate Enhancer

## UPDATED INSTRUCTIONS AND TECHNICAL GUIDANCE TIPS

Please read carefully in full before applying the product and always complete a test patch to check suitability for your surface. For technical support, please call 01268 722500 (Extension Technical Support).

### DESCRIPTION

#### Natural Stone Sealer Ultimate Enhancer

*Suitable for Sandstone. Quick drying easy application*

*High Colour Enhanced Rained on Look*

*Durable, stain-resistant protection*

Our **Ultimate Colour Enhancing Sealer** will transform natural Sandstone\*\* and Indian Sandstone\*\* patios, drives and floors. To avoid trapping in moisture, the sealer is fully breathable and once applied it will leave the surface with that 'just rained on' look, bringing to life the natural rich colours within the stone or slate. The Ultimate Colour Enhancer is a 'colour intensifier' for natural stone surface where the preferred look is when the surface has been rained in and the colours are darkened. **PLEASE NOTE: Not suitable for smooth or polished sandstone.**

### DIRECTIONS FOR USE

**APPLICATION NOTE:** Application on vertical surfaces should be to full saturation commencing at the bottom and working upwards. Do not apply in damp conditions and only apply to dry surfaces in temperatures above 13°C and no higher than 23°C. It is very important to make sure no rain is forecast for at least 8 hours after application.

1. Shake container well before use
2. Ensure that surface area is completely clean from dirt & grime.
3. Allow surface area to dry, will take 3 dry days depending on the weather.
4. Apply 1st coat to saturation by roller, sprayer or brush.
5. Apply 2nd lighter coat wet on wet after 30 mins
6. If over application does occur, please remove excess sealer with a dry sponge or cloth.
7. Avoid walking on surface 4 hours after application and 48 hours for heavy traffic.

### COVERAGE

- Average coverage: 1st coat 5-6m<sup>2</sup> | 2nd coat - 10-15m<sup>2</sup> (dependent on porosity and finish of the surface)

### STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months. Always shake bottle well before use.



### Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
2-3 Hours	2- coats	Roller/ Sprayer/Brush	Undiluted

### PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor. P332+313: If skin irritation occurs: Get medical advice. P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available upon request.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

