

Issue Date 23/09/23

Natural Stone Wet Look

UPDATED INSTRUCTIONS AND TECHNICAL GUIDANCE TIPS

Please read carefully in full before applying the product and always complete a test patch to check suitability for your surface. For technical support, please call 01268 722500 (Extension Technical Support).

DESCRIPTION

Natural Stone Sealer Wet Look

Suitable for popular natural stone types including sandstone, limestone, slate, quarry tile, travertine, granite. Quick drying easy application

Wet Look Silk/Silk Satin Finish

Durable, stain-resistant protection

Smartseal Natural Stone Sealer WET LOOK is a water-based protective sealer that creates a durable, clear silk/satin finish. It can be used on internal and external surfaces made from sandstone** (see exceptions below), limestone, slate, terracotta, quarry and Victorian tiles, brick pavers and any textured stone or masonry surfaces. Smartseal Natural Stone Sealer WET LOOK is rapid drying and very easy to apply. It will provide protection to the applied surface against oil and water-based stains.

WE DO NOT RECOMMEND USING ON POLISHED STONE & CERAMIC GLAZED SURFACES, AS IT WON'T SOAK INTO THE SURFACE

DIRECTIONS FOR USE

APPLICATION NOTE: Application on vertical surfaces should be to full saturation commencing at the bottom and working upwards. Do not apply in damp conditions and only apply to dry surfaces in temperatures above 13°C and no higher than 23°C. It is very important to make sure no rain is forecast for at least 8 hours after application.

Depending on the stone/surface, more than one coat may be required. For most porous stones, a 2nd lighter coat can be applied once touch dry (slightly wet). If over application does occur on either coats, excess sealer can be removed with a dry roller or sponge. Ensure this is done within 45 minutes.

1. Shake container well before use
2. Ensure that surface area is completely clean from dirt & grime.
3. Allow surface area to dry, will take 3 dry days depending on the weather.
4. Apply thin 1st coat to saturation by roller, brush or soft cloth.
5. Apply 2nd lighter 'mist' coat (approx 60 minutes after 1st coat if suitable).
6. If over application does occur, please remove excess sealer with a dry sponge or cloth.
7. Avoid walking on surface 4 hours after application and 48 hours for heavy traffic.

COVERAGE

- Average coverage: 5-12m² (dependant on porosity and finish of the surface)

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months. Always shake bottle well before use.



Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
2-3 Hours	1-2 coats	Roller/ Cloth/Brush	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.

P332+313: If skin irritation occurs: Get medical advice.

P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available upon request.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

