

May 2017

SUPERIOR STONE IMPREGNATOR ECO TECHNICAL APPLICATION GUIDE

DESCRIPTION

RAPID DRYING STONE SEALER

- Can be applied instantly to damp stone & grout
- Fast track formula saves time & money
- Suitable for use on all types of grout, natural stone and porcelain tiles
- Protects against oil & water stains

Superior Stone Enhancer ECO is a premium solvent-based product that offers excellent stain protection against oil and water spills. The advanced formula of **Superior Stone Enhancer ECO** can be applied to damp stone and grout immediately after installation. No waiting around, saving time & money with this unique fast track formula. It penetrates to protect polished porcelain and all types of natural stone surfaces, i.e. travertine, terracotta, limestone, marble, granite, sandstone and many other porous stone surfaces against oil and water-based stains.

DIRECTIONS FOR USE

- 1) Apply a generous, even coat to the surface and edges of the stone using a solvent resistant sprayer, lint free cloth or brush. Ensure even distribution by wiping over several times, remove any surface sealer that has not penetrated the tile or stone after 15-20 minutes.
- 2) Apply a second, allowing 30-45 minutes drying between coats, repeat the process and remove any excess sealer from the applied area with a dry lint free cloth. It will take up to 24 hours before the product will offer full protection. Until this has happened, keep the surface free from water and oil spills, as stains may occur before fully cured.

Please Note: Areas not to be sealed must be protected with masking materials. It is strongly recommended that a test area is completed before proceeding as the sealer may darken or lighten the stone surface.

Expected wear up to 20 years

Varies depending on the type of surface, wear and correct maintenance procedures.

MAINTENANCE

Clean treated areas with **Superior Tile & Stone Cleaner**, do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

COVERAGE

Up to 30m² per litre

This will depend on the porosity of surface. Check the surface after application to ensure full effectiveness of impregnator.

USAGE GUIDELINES

Drying Time	Applications/ Coats	Application Method	Dilution
30-45 mins	1-2 coats	Brush/ Sprayer/ Cloth	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

Highly flammable liquid and vapour. Causes skin irritation. May cause respiratory irritation. Heating may cause a fire or explosion. Harmful if swallowed or if inhaled. Causes serious eye irritation. May cause drowsiness or dizziness.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours. Do not spray on an open flame or other ignition source. Wear protective gloves/ protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Keep out of reach of children. Read label before use. Do not pierce or burn, even after use. Do not get in eyes, on skin, or on clothing. Avoid contact during pregnancy. Wash hands or skin which has come in to contact with product thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. In case of inadequate ventilation wear respiratory protection. If eye irritation persists: Get medical advice.

Product SDS sheet available to download from our website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.


 Made in the UK 