

## Technical Datasheet – Asbestos Roof Coating Primer

### PRODUCT DESCRIPTION

**Asbestos Roof Coating Primer** is a white latex polymer-based emulsion, specially formulated to seal, prime and maximise the adherence of **Asbestos Roof Coating**.

### PURPOSE

Asbestos Coating Primer has been developed to improve safety prior to application of the Asbestos Roof Coating on corrugated asbestos cement roofs. The primer helps to suppress surface dusting as well as inhibit the release and spread of asbestos fibres which could be harmful to health. It will quickly absorb into porous asbestos roof sheeting as well as any cladding constructed from the same material.

### SPECIAL PROPERTIES

- Helps to seal in potentially harmful asbestos fibres
- Improves adherence of Asbestos Roof Coating
- Solvent free - very low VOC content
- Improves water resistance
- For use on internal and external asbestos
- Non-toxic and non-flammable

### APPLICATION INSTRUCTIONS

Only apply once the asbestos has been cleaned and is free from dirt, algae, moss or lichen. Shake container before use. Apply one coat with brush or sprayer to a dry surface in temperatures between 10 - 25 degrees centigrade with no rain forecast. Once dry, then apply the Asbestos Roof Coating.

### COVERAGE

2-3m<sup>2</sup> per litre

### PACKAGING

Smartseal Asbestos Coating Primer is supplied in 5 & 25 litre plastic containers.

### STORAGE

If it is unopened and subject to storing in the correct conditions, the primer has a shelf life of 12 months from the date of manufacture. Store upright above 5 degrees centigrade in original containers, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

### HEALTH AND SAFETY

**Asbestos Roof Coating Primer** is non-toxic and non-flammable. It is recommended safety glasses are worn. Do not smoke. Keep application area well ventilated. Wear PVC gloves and avoid contact with skin.

Refer to the Safety Data Sheet for further information.

### TECHNICAL SERVICES

For further information, call our technical dept on: -

☎ UK 01268 722 500

☎ International +44(0)1268 722500

e-mail  
Web Site

contactus@smartseal.co.uk  
www.smartseal.co.uk

15-11-2023

### Warranty

SmartSeal UK Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst SmartSeal UK Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

*Manufactured by:*

**SmartSeal UK Ltd**  
Unit 3, 65-67 Cutlers Rd, South Woodham Ferrers,  
Chelmsford CM3 5WA, United Kingdom  
[www.smartseal.co.uk](http://www.smartseal.co.uk)  
[contactus@smartseal.co.uk](mailto:contactus@smartseal.co.uk)