

## Technical Datasheet – Black Limestone Sealer

### PRODUCT DESCRIPTION

Smartseal **Black Limestone Sealer** is a highly-effective solvent-based sealer and re-colourant for black limestone which gives a transformative effect.

### PURPOSE

Limestone slabs will often fade over time and gradually turn a lighter shade of grey. The **Black Limestone Sealer** can transform the look of faded limestone patios and make them look like they were recently laid. The sealer can be re-applied at any time to ensure any limestone slabs on patios or other external surfaces look good at all times.

### SPECIAL PROPERTIES

- Transforms the look of your paving and enjoy long-lasting protection
- Preserve the look and appearance of black limestone
- Safeguard colour loss
- UV Resistant

### APPLICATION INSTRUCTIONS

- Clean surface using a pressure washer and/or [Patio Clean Xtreme](#)
- Allow to dry for a minimum of 72 hours
- Apply above 12°C with a temperature no higher than 23°C
- Two coats are recommended
- Apply by roller
- All 2-4 hours between coats (Needs to be touch dry)

Always apply to a test area first to determine suitability. A sample size (150 ml) is available for purchase should you wish to try it before committing to purchase 5 Litres.

**\*\*\*PLEASE NOTE\*\*\*** - For best results, if a sweep-in jointing compound has been used when the slabs were laid, we would recommend using the [residue remover](#) prior to application.

### COVERAGE

Average coverage approx. 4 - 5m<sup>2</sup>/litre first coat (dependant on surface) and approx. 6 - 8m<sup>2</sup>/litre second coat.

### PACKAGING

Smartseal **Black Limestone Sealer** is supplied in 150ml Sample & 5L metal containers.

### STORAGE

Store in cool, dry conditions out of direct sunlight in original container only. USE WITHIN 6 MONTHS OF PURCHASE & WITHIN 3 MONTHS ONCE OPENED.

### HEALTH AND SAFETY

SmartSeal Black limestone Sealer is a solvent-based acrylic sealer, which is highly flammable. It is recommended safety glasses are worn. Do not smoke. Keep application area well ventilated. Wear PVC gloves and avoid contact with skin and a FFP3 facemask.

Refer to the Safety Data Sheet for further information.

### TECHNICAL SERVICES

For further information, call our technical dept on:

☐ International +44(0)1268 722500

☐ UK 01268 722 500

e-mail  
Web Site

contactus@smartseal.co.uk  
www.smartseal.co.uk

12-09-2023

### Warranty

SmartSeal UK Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst SmartSeal UK Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

### Manufactured by:

SmartSeal UK Ltd  
Unit 3, 65-67 Cutlers Rd, South Woodham Ferrers,  
Chelmsford CM3 5WA, United Kingdom  
[www.smartseal.co.uk](http://www.smartseal.co.uk)  
contactus@smartseal.co.uk