

# **MULTI Pro 9 - 12**



The **IK MULTI Pro 9-12 sprayers** are characterised by maximum performance in terms of ergonomics, ease of use and safety. They offer a professional spraying solution to achieve optimal results in a wide range of sectors.

They are designed for maximum strength and versatility with the most aggressive chemicals. Particularly resistant to acids.



#### Sectors in which to use

- Building
- Cleaning and disinfection
- Industry and maintenance
- Automotive and detailing
- Pest control
- Epidemics & virus control
- Air conditioning (HVAC)

#### Products with which to use

optimal Disinfectants, neutral products, acids

Solvent-based pesticides, alcohols, oils, solvents and petroleum by-products



#### IK MULTI/ IK MULTI Pro

Oils, solvents and petroleum by-products

Alkalis and ketones

X

Disinfectants

~

Solvent based pesticides

L

Neutral products

**L** Optimal **✓** Limited

Acids

Alcohols

#### **Technical information**

Technical information	MULTI Pro 9	MULTI Pro 12
VALVE	Tared at 3 bar / 43.5 psi depressurizable with automatic depressurization option	
HOSE	1.5m / 59 inches	
STANDARD NOZZLES	Adjustable conical nozzle and fan	
LANCE	47 cm / 18.5 inches fibreflass	
USEFUL CAPACITY	6L 1.58 U.S. Gals.	8L 2.11 U.S. Gals.
TOTAL CAPACITY	8L 2.11 U.S. Gals.	10L 2.64 U.S. Gals.
LITRES/MIN. 3 BAR	0.7 l/min 0.18 gal/min.	
GROSS WEIGHT	2.71 kg - 5.97 lbs.	2.99 kg - 6.59 lbs.
NET WEIGHT	2.33 kg - 5.13 lbs.	2.57 kg - 5.66 lbs.

## **Logistics data**

Logistics data	MULTI Pro 9	MULTI Pro 12
CODE	8.26.72	8.26.71
EAN	84.14685.10202.7	84.14685.10201.0
CONDITIONING	1 unit	
UNITS PER PALLET	28 units	
DIMENSIONS PER PALLET	1200 x 800 x 1050	

### **Functional information**



INOX / SST handle



Safety lock



Integrated funnel in tank



Parking for lance



Pump fastening system during filling



Safety valve with depressurisation option



**X** Not valid

Content identifying system



Transport belt in shoulder strap



Translucent tank with level indicator



Base with support for the feet



