



January 2023

FOR RETAIL & PROFESSIONAL USE

Tarmac Liquid Crack Filler

DESCRIPTION

Smartseal Tarmac Liquid Crack Filler is a polymer modified flexible crack filler for asphalt, tarmac and all bituminous surfaces.

Smartseal Tarmac Liquid Crack Filler is a polymer modified flexible crack filler for asphalt, tarmac and all bituminous surfaces.

DIRECTIONS FOR USE

Sweep or scrape out loose debris from the crack.

Mix well before and decant into a spouted jug. Do not use in wet or cold conditions below 5°C. For cracks up to 3mm, sweep or scrape out loose debris and pour into the cracks using the spouted jug. For cracks 3mm - 25mm wide: prime the sides of the crack with a thin coat of the crack filler. Mix the crack filler with damp sand to produce a slightly stiff mortar and paste into the crack. Smooth off and allow to dry. Drying time depends on weather conditions and crack size. Ensure the temperature is warm and dry to avoid complications. Allow approximately 24 hours for cracks up to 3mm and an average of 8-10 hours for cracks around 25mm.

All product labels provide general safety information. Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.

Available direct from Smartseal UK. All products are sold subject to the Company's Standard Conditions of Sale.

Please Note: This product is designed for use on bitumen based surfaces. It could soften surfaces which contain coal tar. If in doubt, apply a test area and check after 24 hours that no softening has occurred. Use water and detergent if the product has not dried. Once dried, use white spirit. 12 months in unopened container. Protect from frost and direct sunlight. Do not allow to freeze.

COVERAGE

5 litres will fill 100 linear metres of cracks at 5mm wide & 5mm deep.

Usage Guidelines

Pack Size	Suitable For	Application Method	Usage
1L & 5L	Tarmac/Asphalt	Jug	Interior/Exterior

PERFORMANCE & BENEFITS

- ✓ Ready to Use – Simple Pour-On Application
- ✓ Penetrates & Seals Cracks in Tarmac
- ✓ Flexible Repair That Moves With the Surface
- ✓ Flexible Repair That Moves With the Surface

HANDLING & STORAGE

Use within 6 months of purchase or production date. Store in cool, dry conditions out of direct sunlight in original container only. DO NOT RE-USE CONTAINER.

