

1. SECTION 1: Identification of the substance/mixture and of the company/undertaking

2.1.1. Product identifier

Product form : Mixture
 Trade name LIQUID ROOF REPAIR
 UFI : 4300-D0C3-U00E-2S4K

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Intended for general public
 Main use category : Industrial use, Professional use, Consumer use
 Use of the substance/mixture : Paint

1.3. Details of the supplier of the safety data sheet

SMARTSEAL
 UNIT 3
 65-67 CUTLERS ROAD
 SOUTH WOODHAM FERRERS
 CHELMSFORD
 ESSEX
 T 01268 722500
contactus@smartseal.co.uk www.smartseal.co.uk

1.4. Emergency telephone number

Emergency number : 01268 722500 (Mon – Fri 08:30 – 16:30 only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
 Specific target organ toxicity – Single exposure, Category 3, H336
 Narcosis
 Hazardous to the aquatic environment – Chronic Hazard, H412
 Category 3

Full text of H- and EUH-statements: see section 16


Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Warning

Contains

: HYDROCARBONS, C9, Aromatics; Low Aromatic White Spirit

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
 H336 - May cause drowsiness or dizziness.
 H412 - Harmful to aquatic life with long lasting effects.
 Precautionary statements (CLP)
 : P102 - Keep out of reach of children.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
 P261 - Avoid breathing vapours.

LIQUID ROOF REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

	P280 - Wear protective clothing, eye protection, face protection. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
CALCIUM CARBONATE substance with national workplace exposure limit(s) (GB)	CAS-No.: 1317-65-3 EC-No.: 215-279-6	20 – 30	Not classified
Low Aromatic White Spirit	CAS-No.: 64742-48-9 EC-No.: 265-150-3 EC Index-No.: 649-327-00-6	15-30	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
HYDROCARBONS, C9, Aromatics	EC-No.: 918-668-5 REACH-no: 01-2119455851-35	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Titanium Dioxide substance with national workplace exposure limit(s) (GB)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2	5 – 20	Not classified

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: Take off contaminated clothing. Gently wash with plenty of soap and water.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water. Get medical advice/attention.
First-aid measures after ingestion	: If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause moderate irritation.
Symptoms/effects after eye contact	: May cause eye irritation.

LIQUID ROOF REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water spray.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Explosion hazard : Heating may cause a fire or explosion.
Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection. Evacuate area. Get the package away from the fire if this can be done without risk. Use water spray or fog for cooling exposed containers.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing. Wear fire/flame resistant/retardant clothing. EN 469.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Act in accordance with local emergency plan. Evacuate unnecessary personnel. Do not touch or walk on the spilled product. Notify fire brigade and environmental authorities.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment.

6.2. Environmental precautions

Do not allow product to spread into the environment. Do not allow to enter drains or water courses. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain large spillage with sand or earth.
Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Avoid contact with skin and eyes. Use personal protective equipment as required. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
Hygiene measures : Do not eat, drink or smoke when using this product. Take off immediately all contaminated clothing and wash it before reuse. Wear personal protective equipment.

LIQUID ROOF REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container closed when not in use. Direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible products : Oxidizing agent. Strong bases. Strong acids.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

CALCIUM CARBONATE (1317-65-3)

United Kingdom - Occupational Exposure Limits

Local name	Calcium carbonate (Limestone, Marble)
WEL TWA (OEL TWA)	10 mg/m ³ total inhalable 4 mg/m ³ respirable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Titanium Dioxide (13463-67-7)

United Kingdom - Occupational Exposure Limits

Local name	Titanium dioxide
WEL TWA (OEL TWA)	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure that there is a suitable ventilation system. Provide adequate ventilation to minimize dust concentrations.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Chemical goggles or safety glasses

Skin protection

Skin and body protection:

Chemical resistant safety shoes. Wear protective clothing

Hand protection:

Wear protective gloves

LIQUID ROOF REPAIR HB

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)			EN 374-3

Other skin protection

Materials for protective clothing:

Wear protective clothing

Respiratory protection

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Respiratory protection			
Device	Filter type	Condition Dust	Standard
Disposable half mask	Type P2	protection	EN 143

Environmental exposure controls

Environmental exposure controls:

Do not exceed the occupational exposure limits (OEL). Avoid creating or spreading dust.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various colours.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: ≥ 140 °C
Flammability	: Flammable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 40 °C
Auto-ignition temperature	: ≥ 400 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Soluble in organic solvents.
	Water: Non-soluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: > 1.2 g/cm ³
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content	: EU Limit value for this product (cat.A/i): 500g/l (2010). This product contains max. 499g/l VOC
-------------	---

LIQUID ROOF REPAIR

Safety Data

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified :
Acute toxicity (dermal) Not classified :
Acute toxicity (inhalation) Not classified

HYDROCARBONS, C9, Aromatics

LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 6.193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

CALCIUM CARBONATE (1317-65-3)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

Titanium Dioxide (13463-67-7)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	> 6.8 mg/l/4h

Skin corrosion/irritation : Not classified

Titanium Dioxide (13463-67-7)

pH	7
----	---

Serious eye damage/irritation : Not classified

Titanium Dioxide (13463-67-7)

pH	7
----	---

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

LIQUID ROOF REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HYDROCARBONS, C9, Aromatics

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

Low Aromatic White Spirit (64742-48-9)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

HYDROCARBONS, C9, Aromatics

NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
----------------------------	---

Aspiration hazard	: Not classified
-------------------	------------------

HYDROCARBONS, C9, Aromatics

Viscosity, kinematic	1.06 mm ² /s Temp.: '20°C' Parameter: 'cStcSt'
----------------------	---

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
--	------------------

Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
---	--

HYDROCARBONS, C9, Aromatics

LC50 - Fish [1]	9.2 mg/l
EC50 - Crustacea [1]	3.2
EC50 72h - Algae [1]	2.9 mg/l
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC chronic crustacea	2.14 mg/l 21 days

CALCIUM CARBONATE (1317-65-3)

LC50 - Fish [1]	> 10000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l
EC50 72h - Algae [1]	> 200 mg/l

Titanium Dioxide (13463-67-7)

LC50 - Fish [1]	> 10000 mg/l
EC50 - Crustacea [1]	> 10000 mg/l
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

LIQUID RUBBER

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

LIQUID ROOF REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HYDROCARBONS, C9, Aromatics

Persistence and degradability	Not rapidly degradable
Biodegradation	78 % 28 days

Low Aromatic White Spirit (64742-48-9)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

CALCIUM CARBONATE (1317-65-3)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Titanium Dioxide (13463-67-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Must follow special treatment according to local regulation.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III	UN 1263 Paint, 3, III	UN 1263 PAINT, 3, III	UN 1263 PAINT, 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3

LIQUID ROOF REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	
Vehicle for tank carriage	: LGBF :
Transport category (ADR)	: FL
Special provisions for carriage - Packages (ADR)	: 3
Special provisions for carriage - Operation (ADR)	: V12
Hazard identification number (Kemler No.)	: S2
Orange plates	: 30
	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: 3YE

Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355

LIQUID ROOF REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192 :
ERG code (IATA)	3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001 :
Special packing provisions (RID)	PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

LIQUID ROOF REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

VOC Directive (2004/42)

Organic solvent : Yes
VOC content : EU Limit value for this product (cat.A/i): 500g/l (2010). This product contains max. 499g/l VOC

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.