

## SOLVENT FREE IMPREGNATING SEALER FOR CLAY TILES AND PAVERS

### Product Description

**Smartseal Clay Tile Sealer** is a unique acrylic oil and water repellent treatment for use on most types of Clay Tiles and pavers.

It is totally safe and non-hazardous to children and pets. It contains biodegradable ingredients that does not include any bleach or acid contents.

### Advantages

Due to its excellent water repellent qualities, it reduces penetration of oil and water, frost damage and organic growth. Stain and dirt resistant. Non-stick and allows easy chewing gum removal. Conforms to BS6477:1992. Will not affect the original colour of the substrate. Highly resistant to weathering and UV exposure. Moisture vapour permeable. Non-glossy appearance. Unaffected by freeze/thaw cycles. One application required reducing labour costs.

### Areas For Use

For use on most types of Clay tiles and some other forms of natural stone.

### Colour Range

Dry or Wet Look finish

### Colour Rates

Sandstone.....5m<sup>2</sup>/litre  
Facing brickwork. 5m<sup>2</sup>/litre  
Concrete.....5m<sup>2</sup>/litre  
Concrete block work 3m<sup>2</sup>/litre  
Reconstructed stone 3m<sup>2</sup>/litre

### Drying Times

Touch dry:.....4 hours  
Waterproof:.... 24-48 hours

### Preparation

Ensure surfaces to be treated are clean, free from contamination and dry. Treat all areas affected by organic growth with Smartseal Moss Cleaner or Fungicidal Wash.

**\*\*ALWAYS DO A TEST AREA FIRST TO TEST SURFACE SUITABILITY**



## Application

**We always recommend doing a test area first as the product can dry differently on some substrates creating a slightly darker appearance.**

Impregnation to be applied by flood-coating method using a low pressure spray equipment of the knapsack type, or by brush/roller. Application on vertical surfaces should be to full saturation commencing at the bottom and working upwards. Two applications are required on wood with only one application required on masonry, brickwork etc. Do not apply at temperatures below 5°C. Shake container well before use.

## Cleaning

All equipment should be cleaned with water immediately after use.

## Storage

Store away from direct sunlight. protect from frost. Store only in original containers.

## Shelf Life

This product should be used within 12months of manufacture.

## Health & Safety

Refer to Health and Safety sheets.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*