



APPLICATION GUIDE FOR SMARTSEAL TARMAC RESTORER

PREPARATION

- Before any application of Tarmac restorer, ensure the surface thoroughly cleaned and loose stones swept away.
- Clean the tarmac by power/jet washing on reduced pressure to avoid damage to the surface.
- If algae or moss is present a pre-treatment with Smartseal fungicidal wash is advised.

APPLICATION GUIDELINES

- Apply product to a clean, dry tarmac surface with temperatures above 10 degrees and no rain is forecast for at least 3 hours after application process has finished.
- For best results it is advisable to use a long handled roller kit with a medium pile head. A soft broom or paint brush can be used for borders or hard to get to areas, but generally a roller kit is best.
- Dependent on condition two coats of tarmac restorer are recommended. Average coverage ratios are 40-60sq.* metres per 20 litre drum (60 sq. metres if the tarmac is in good condition but has lost colour and faded over time. 40 sq. metres for poorer quality tarmac surfaces).
- Prior to commencing application thoroughly stir the tarmac restorer. This will ensure the pigment and the anti-slip additive within the product are mixed thoroughly and not settled at the bottom of the container. This mixing can be carried out with anything from a stiff stick, broom handle, or a mixing paddle connected to an electric drill.
- Areas adjacent to neighbours driveways, flower beds or lawns should be masked off with tape, or planks of wood to avoid un-wanted coverage.

- After application keep vehicles and foot traffic of the Tarmac until completely dry. If the surface requires two coats of Tarmac restorer ensure initial coat is touch dry before subsequent application (usually 2-3 hours)

MAINTENANCE

Any ongoing maintenance should be restricted to a gentle sweep and a wash down once or twice a year.

The Tarmac restorer itself is a very durable product, but as with any other external product will require re-application from time to time. For driveways that receive an average amount of traffic, a top up coat of Tarmac restorer is recommended on average, every 5 years.

For tarmac driveways that are more heavily trafficked or are in very shady, damp conditions more frequent top up coats may be necessary.

For further assistance please contact our technical department on **01268 722504**

