SmartSeal Superior Surface Protection

September 2025

FOR PROFESSIONAL USE

Resin Bound Sealer Technical Datasheet

DESCRIPTION

UV RESISTANT - RESIN BONDER SEALER - DRIVES, PATHS, PATIOS, NON TOXIC OIL RESISTANT

Rejuvenates Resin Bound & Bonded Surfaces, Protects from Algae, Moss, Dirt, Colour Loss & Staining.A Ready and Easy To Apply Non-Toxic Formula giving a Hardwearing solution. Suitable for Driveways, Patios and Pathways.
Sealing a resin-bound or bonded surface is recommended to add life-span to the surface by a number of years. Sealing the surface not only enhances the appearance, restoring the "wet look" but it will most importantly add a protective barrier against a number of elements that can reduce the overall condition.

For cleaning and maintenance to the Resin sealer, the Smartseal **Premium Resin Bound Cleaner** is recommended in addition to ensure max product benefits are obtained from the sealer.

DIRECTIONS FOR USE

1) Prep & Test - Surface must be clean and dry. Apply only if >12°C with no rain for 4 hours. Alway test in a small area first.

2) Apply Sparingly - Use a acetone sprayer or a roller. Aim for 4 - 5m^2 per litre. Avoiddirect sunlight or tempretures above 23oc.

3) Optional Recoat - Once touch dry, apply a secong lighter coat if the surface is highly porous or aged.



Please Note: should always be applied to a test area first to ensure suitability and colour.

COVERAGE

Up to 4m^2 - 5m^2 per lire.
Coverage varies depending on surface porosity.

Usage Guidelines

Finish	Drying Time	Application Method	Tempretures
Wet Look	1 hour Walking 8 Hours Vehicle	Acetone Sprayer/Roller	Do not apply above 23°C

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS
E:H226 - Flammable liquid and vapour.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.
:P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing vapours.
P280 - Wear protective clothing, eye protection, face protection.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
:EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

FOR USE BY PROFESSIONAL OPERATORS

HANDLING & STORAGE

Use within 6 months of purchase or production date. Store in cool, dry conditions out of direct sunlight in original container only. DO NOT RE-USE CONTAINER.



SmartSeal UK Ltd
Unit 3 65 - 67 Cutlers Road South Woodham Ferrers Chelmsford Essex CM3 5WA
United Kingdom
Tel: +44 (0)1268 722 500
Email: contactus@smartseal.co.uk
Web: www.smartseal.co.uk

MADE IN THE UK